


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:219.88V I:0.1471A P:31.202W PF:0.9649 Freq:49.99Hz Lamp Flux:2734.69x1 lm		
NAME: R6836-12PDM	TYPE:R6836-12PDM	WEIGHT:
SPEC.:4FT	DIM.: 4FT	SERIAL No.:1
MFR.: BLUEVISION	SUR.:1220*50	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 87.65 lm/W			
MODEL	R6836-12PDM	I _{max} (cd)	1125	S/MH (C0/180)	1.10
NOMINAL POWER(W)	31.79	LOR(%)	100.0	S/MH (C90/270)	1.19
RATED VOLTAGE(V)	220	TOTAL FLUX(lm)	2734.7	η UP,DN(C0-180)	0.6,49.7
NOMINAL FLUX(lm)	2734.69	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.6,49.1
LAMPS INSIDE	1	η up (%)	1.2	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	220	η down (%)	98.8	CIBSE SHR MAX	1.30

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:KEVINLI
Test Date:2017-12-23

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.400
Humidity:65.0%
Test Distance:7.310m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	1099	1100	1097	1088	1081	1087	1096	1100	0- 10	105.9	105.9	3.87,3.87
20	1004	1016	1016	992.3	971.9	991.2	1016	1014	10- 20	297.0	402.8	14.7,14.7
30	859.2	882.1	893.0	852.2	818.5	850.7	891.9	880.9	20- 30	432.0	834.8	30.5,30.5
40	691.5	720.4	739.5	688.1	649.0	687.1	738.9	719.7	30- 40	492.1	1327	48.5,48.5
50	524.6	551.0	571.6	519.6	483.4	519.5	572.3	551.3	40- 50	478.8	1806	66,66
60	368.4	387.5	402.6	357.3	327.9	358.0	404.1	388.4	50- 60	406.8	2212	80.9,80.9
70	222.7	233.2	238.7	204.0	183.7	205.3	241.4	235.0	60- 70	293.3	2506	91.6,91.6
80	92.18	93.58	90.02	69.73	60.26	71.15	92.90	95.00	70- 80	157.5	2663	97.4,97.4
90	5.520	4.356	2.842	2.663	2.338	2.459	2.838	4.783	80- 90	38.16	2701	98.8,98.8
100	3.000	3.135	3.512	3.362	2.876	3.070	3.238	2.873	90-100	3.109	2704	98.9,98.9
110	3.809	3.958	4.397	4.259	3.603	3.845	4.070	3.588	100-110	3.721	2708	99,99
120	4.818	4.915	5.378	5.276	4.519	4.750	4.940	4.429	110-120	4.349	2713	99.2,99.2
130	5.997	6.025	6.446	6.420	5.573	5.745	5.870	5.383	120-130	4.813	2717	99.4,99.4
140	7.210	7.098	7.469	7.482	6.749	6.836	6.863	6.442	130-140	4.994	2722	99.5,99.5
150	8.298	8.141	8.399	8.451	7.899	7.913	7.886	7.526	140-150	4.727	2727	99.7,99.7
160	9.384	9.099	9.261	9.401	9.031	9.015	8.871	8.614	150-160	3.952	2731	99.9,99.9
170	10.22	9.847	9.919	10.00	10.09	9.786	9.704	9.598	160-170	2.681	2734	100,100
180	10.66	10.23	10.17	10.22	10.70	10.26	10.18	10.21	170-180	0.9616	2735	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:KEVINLI
 Test Date:2017-12-23

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.400
 Humidity:65.0%
 Test Distance:7.310m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:219.88V I:0.1471A P:31.202W PF:0.9649 Freq:49.99Hz Lamp Flux:2734.69x1 lm		
NAME: R6836-12PDM	TYPE:R6836-12PDM	WEIGHT:
SPEC.:4FT	DIM.: 4FT	SERIAL No.:1
MFR.: BLUEVISION	SUR.:1220*50	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:KEVINLI
Test Date:2017-12-23

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.400
Humidity:65.0%
Test Distance:7.310m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:219.88V I:0.1471A P:31.202W PF:0.9649 Freq:49.99Hz Lamp Flux:2734.69x1 lm		
NAME: R6836-12PDM	TYPE:R6836-12PDM	WEIGHT:
SPEC.:4FT	DIM.: 4FT	SERIAL No.:1
MFR.: BLUEVISION	SUR.:1220*50	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.99
1.0	1.05	1.00	.97	1.02	.98	.95	.98	.95	.92	.94	.91	.89	.90	.88	.86	.84
2.0	.92	.85	.80	.90	.84	.79	.86	.81	.77	.83	.78	.75	.79	.76	.73	.71
3.0	.81	.73	.67	.79	.72	.66	.76	.70	.65	.73	.68	.64	.71	.66	.62	.60
4.0	.72	.64	.57	.71	.63	.57	.68	.61	.56	.66	.60	.55	.63	.58	.54	.52
5.0	.65	.56	.50	.64	.55	.49	.61	.54	.49	.59	.53	.48	.57	.52	.47	.45
6.0	.59	.50	.44	.58	.49	.43	.56	.48	.43	.54	.47	.42	.52	.46	.42	.40
7.0	.53	.45	.39	.52	.44	.39	.51	.43	.38	.49	.43	.38	.48	.42	.37	.36
8.0	.49	.40	.35	.48	.40	.35	.47	.39	.34	.45	.39	.34	.44	.38	.34	.32
9.0	.45	.37	.31	.44	.37	.31	.43	.36	.31	.42	.35	.31	.41	.35	.31	.29
10.0	.41	.34	.29	.41	.33	.28	.40	.33	.28	.39	.33	.28	.38	.32	.28	.26



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:KEVINLI
 Test Date:2017-12-23

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.400
 Humidity:65.0%
 Test Distance:7.310m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:219.88V I:0.1471A P:31.202W PF:0.9649 Freq:49.99Hz Lamp Flux:2734.69x1 lm					
NAME: R6836-12PDM			TYPE:R6836-12PDM		WEIGHT:
SPEC.:4FT			DIM.: 4FT		SERIAL No.:1
MFR.: BLUEVISION			SUR.:1220*50		Shielding Angle:

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.291	.166	.053	.284	.162	.051	.270	.155	.049	.257	.148	.048	.246	.142	.046		
2.0	.276	.151	.046	.270	.149	.046	.258	.143	.045	.246	.138	.043	.236	.134	.042		
3.0	.257	.137	.041	.252	.135	.041	.241	.130	.040	.231	.126	.039	.222	.123	.038		
4.0	.239	.124	.036	.234	.122	.036	.224	.119	.035	.215	.115	.035	.207	.112	.034		
5.0	.221	.113	.033	.217	.111	.032	.208	.109	.032	.200	.106	.031	.193	.103	.031		
6.0	.206	.103	.030	.202	.102	.029	.194	.100	.029	.187	.097	.029	.181	.095	.028		
7.0	.192	.095	.027	.189	.094	.027	.182	.092	.026	.176	.090	.026	.170	.088	.026		
8.0	.180	.088	.025	.177	.087	.025	.171	.085	.024	.165	.084	.024	.160	.082	.024		
9.0	.169	.082	.023	.166	.081	.023	.161	.079	.023	.155	.078	.022	.151	.076	.022		
10.0	.159	.076	.021	.157	.076	.021	.152	.074	.021	.147	.073	.021	.142	.072	.021		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.200	.200	.200	.171	.171	.171	.117	.117	.117	.067	.067	.067	.021	.021	.021	
1.0	.188	.166	.145	.161	.142	.125	.110	.098	.086	.063	.057	.050	.020	.018	.016	
2.0	.180	.141	.109	.154	.122	.094	.105	.084	.066	.061	.049	.039	.020	.016	.013	
3.0	.172	.124	.086	.147	.107	.074	.101	.074	.052	.058	.043	.031	.019	.014	.010	
4.0	.164	.110	.069	.141	.095	.060	.097	.066	.042	.056	.039	.025	.018	.013	.008	
5.0	.156	.100	.058	.134	.086	.050	.092	.060	.036	.054	.035	.021	.017	.012	.007	
6.0	.149	.091	.050	.128	.079	.043	.089	.055	.031	.051	.033	.018	.017	.011	.006	
7.0	.143	.084	.044	.123	.073	.038	.085	.051	.027	.049	.030	.016	.016	.010	.005	
8.0	.136	.079	.039	.117	.068	.034	.081	.048	.024	.047	.028	.014	.015	.009	.005	
9.0	.130	.074	.035	.112	.064	.031	.078	.045	.022	.045	.027	.013	.015	.009	.004	
10.0	.125	.069	.033	.108	.060	.028	.075	.042	.020	.044	.025	.012	.014	.008	.004	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:KEVINLI
Test Date:2017-12-23

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.400
Humidity:65.0%
Test Distance:7.310m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:219.88V I:0.1471A P:31.202W PF:0.9649 Freq:49.99Hz Lamp Flux:2734.69x1 lm											
NAME: R6836-12PDM						TYPE:R6836-12PDM			WEIGHT:		
SPEC.:4FT						DIM.: 4FT			SERIAL No.:1		
MFR.: BLUEVISION						SUR.:1220*50			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H		18.0	19.5	18.3	19.7	19.9	18.4	19.9	18.7	20.1	20.3
	3H	19.4	20.7	19.7	21.0	21.2	19.8	21.1	20.1	21.4	21.7
	4H	19.9	21.2	20.2	21.5	21.7	20.3	21.6	20.7	21.9	22.1
	6H	20.3	21.5	20.6	21.8	22.1	20.7	21.9	21.0	22.1	22.4
	8H	20.4	21.6	20.8	21.9	22.2	20.7	21.9	21.1	22.2	22.5
	12H	20.5	21.6	20.8	21.9	22.2	20.8	21.9	21.1	22.2	22.5
4H	2H	18.6	19.9	19.0	20.2	20.4	19.0	20.2	19.3	20.5	20.8
	3H	20.2	21.3	20.5	21.6	21.9	20.5	21.6	20.9	21.9	22.3
	4H	20.8	21.8	21.2	22.2	22.5	21.2	22.2	21.6	22.5	22.9
	6H	21.3	22.2	21.7	22.6	23.0	21.6	22.5	22.0	22.9	23.3
	8H	21.5	22.3	21.9	22.7	23.1	21.7	22.6	22.2	23.0	23.4
	12H	21.6	22.4	22.0	22.8	23.2	21.8	22.6	22.3	23.0	23.4
8H	4H	21.1	21.9	21.5	22.3	22.7	21.4	22.2	21.8	22.6	23.0
	6H	21.7	22.4	22.2	22.8	23.3	22.0	22.7	22.4	23.1	23.5
	8H	22.0	22.6	22.4	23.0	23.5	22.2	22.8	22.7	23.2	23.7
	12H	22.1	22.7	22.6	23.1	23.6	22.3	22.8	22.8	23.3	23.8
12H	4H	21.1	21.8	21.5	22.2	22.7	21.4	22.1	21.8	22.5	23.0
	6H	21.8	22.4	22.2	22.8	23.3	22.0	22.6	22.5	23.1	23.5
	8H	22.0	22.6	22.5	23.0	23.5	22.2	22.8	22.7	23.2	23.7
Variations with the observer position at spacings:											
S = 1.0H	+ 0.2 / - 0.2					+ 0.2 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.3					+ 0.3 / - 0.3					

CIE Pub.117, 2735 lm Total Lamp Luminous Flux Correct ($8\log(F/F_0) = 3.5$)

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:KEVINLI
Test Date:2017-12-23

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.400
Humidity:65.0%
Test Distance:7.310m [K=1.0000]
Remarks:


```

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.400
Humidity:65.0%
Test Distance:7.310m [K=1.0000]
Remarks:

```

ISOCANDELA DIAGRAM

Test:U:219.88V I:0.1471A P:31.202W PF:0.9649 Freq:49.99Hz Lamp Flux:2734.69x1 lm		
NAME: R6836-12PDM	TYPE:R6836-12PDM	WEIGHT:
SPEC.:4FT	DIM.: 4FT	SERIAL No.:1
MFR.: BLUEVISION	SUR.:1220*50	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:KEVINLI
Test Date:2017-12-23

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.400
Humidity:65.0%
Test Distance:7.310m [K=1.0000]
Remarks:

AAI Figure

Test:U:219.88V I:0.1471A P:31.202W PF:0.9649 Freq:49.99Hz Lamp Flux:2734.69x1 lm		
NAME: R6836-12PDM	TYPE:R6836-12PDM	WEIGHT:
SPEC.:4FT	DIM.: 4FT	SERIAL No.:1
MFR.: BLUEVISION	SUR.:1220*50	Shielding Angle:




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: KEVINLI
Test Date: 2017-12-23

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.400
Humidity: 65.0%
Test Distance: 7.310m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:219.88V I:0.1471A P:31.202W PF:0.9649 Freq:49.99Hz Lamp Flux:2734.69x1 lm		
NAME: R6836-12PDM	TYPE:R6836-12PDM	WEIGHT:
SPEC.:4FT	DIM.: 4FT	SERIAL No.:1
MFR.: BLUEVISION	SUR.:1220*50	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:KEVINLI
Test Date:2017-12-23

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.400
Humidity:65.0%
Test Distance:7.310m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:219.88V I:0.1471A P:31.202W PF:0.9649 Freq:49.99Hz Lamp Flux:2734.69x1 lm		
NAME: R6836-12PDM	TYPE:R6836-12PDM	WEIGHT:
SPEC.:4FT	DIM.: 4FT	SERIAL No.:1
MFR.: BLUEVISION	SUR.:1220*50	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	10638
L_0~180 (75) av	8629
L_0~180 (85) av	5339
L_90~270 (65) av	12438
L_90~270 (75) av	10289
L_90~270 (85) av	6551
L_45 (65) av	11439
L_45 (75) av	9331
L_45 (85) av	5782

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:KEVINLI
Test Date:2017-12-23

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.400
Humidity:65.0%
Test Distance:7.310m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: KEVINLI
Test Date: 2017-12-23

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.400
Humidity: 65.0%
Test Distance: 7.310m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:219.88V I:0.1471A P:31.202W PF:0.9649 Freq:49.99Hz Lamp Flux:2734.69x1 lm		
NAME: R6836-12PDM	TYPE:R6836-12PDM	WEIGHT:
SPEC.:4FT	DIM.: 4FT	SERIAL No.:1
MFR.: BLUEVISION	SUR.:1220*50	Shielding Angle:

Table--1

UNIT: cd

C (DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	1124	1124	1124	1124	1124	1124	1124	1124	1124	1124	1124	1124	1124	1124	1124	1124			
5	1120	1121	1120	1119	1117	1116	1114	1112	1111	1111	1113	1115	1117	1118	1120	1120			
10	1099	1101	1100	1100	1097	1093	1088	1084	1081	1082	1087	1091	1096	1099	1100	1098			
15	1059	1063	1065	1067	1063	1057	1047	1039	1034	1035	1046	1055	1062	1064	1064	1059			
20	1004	1010	1016	1021	1016	1009	992	980	972	975	991	1005	1016	1018	1014	1005			
25	936	944	954	964	959	949	927	909	899	904	925	945	958	960	952	939			
30	859	868	882	897	893	880	852	830	819	825	851	875	892	893	881	863			
35	776	787	803	822	819	804	772	747	734	742	770	799	818	817	802	782			
40	691	702	720	742	740	723	688	662	649	657	687	719	739	737	720	697			
45	607	617	636	658	657	640	604	578	565	573	603	635	656	654	635	613			
50	525	534	551	573	572	555	520	495	483	491	519	551	572	569	551	530			
55	445	453	468	488	487	470	438	415	404	411	438	467	488	485	469	449			
60	368	376	388	405	403	387	357	338	328	334	358	384	404	402	388	372			
65	294	300	309	322	320	305	279	263	254	259	281	303	322	320	310	297			
70	223	227	233	243	239	226	204	191	184	188	205	224	241	241	235	224			
75	155	158	160	166	161	150	133	123	118	121	134	149	164	164	162	155			
80	92.2	93.9	93.6	95.2	90.0	81.2	69.7	64.2	60.3	61.9	71.1	80.8	92.9	94.4	95.0	91.3			
85	39.9	40.5	38.7	37.9	33.8	28.1	21.8	19.1	16.9	17.6	22.7	27.9	35.8	37.6	39.8	38.5			
90	5.52	5.62	4.36	3.62	2.84	2.78	2.66	2.59	2.34	2.35	2.46	2.54	2.84	3.45	4.78	4.64			
95	2.68	2.70	2.80	3.01	3.11	3.13	3.00	2.90	2.58	2.60	2.73	2.82	2.86	2.72	2.56	2.42			
100	3.00	3.03	3.14	3.37	3.51	3.51	3.36	3.26	2.88	2.92	3.07	3.18	3.24	3.06	2.87	2.70			
105	3.39	3.41	3.53	3.78	3.95	3.94	3.79	3.67	3.21	3.26	3.44	3.56	3.63	3.43	3.21	3.02			
110	3.81	3.83	3.96	4.22	4.40	4.39	4.26	4.12	3.60	3.66	3.84	3.98	4.07	3.83	3.59	3.38			
115	4.29	4.30	4.41	4.67	4.88	4.85	4.75	4.63	4.04	4.10	4.29	4.40	4.50	4.24	3.99	3.79			
120	4.82	4.80	4.92	5.13	5.38	5.35	5.28	5.18	4.52	4.58	4.75	4.84	4.94	4.66	4.43	4.22			
125	5.37	5.36	5.46	5.65	5.90	5.88	5.84	5.75	5.02	5.07	5.23	5.27	5.39	5.10	4.90	4.72			
130	6.00	5.96	6.03	6.18	6.45	6.44	6.42	6.38	5.57	5.62	5.74	5.74	5.87	5.57	5.38	5.24			
135	6.61	6.57	6.59	6.73	6.97	7.00	6.98	6.99	6.16	6.19	6.29	6.27	6.36	6.06	5.89	5.81			
140	7.21	7.17	7.10	7.24	7.47	7.54	7.48	7.53	6.75	6.78	6.84	6.84	6.86	6.59	6.44	6.39			
145	7.75	7.76	7.62	7.74	7.94	8.06	7.97	8.05	7.32	7.33	7.37	7.38	7.37	7.12	6.99	6.97			
150	8.30	8.28	8.14	8.17	8.40	8.58	8.45	8.52	7.90	7.90	7.91	7.95	7.89	7.64	7.53	7.56			
155	8.83	8.83	8.65	8.63	8.84	8.91	8.93	8.97	8.46	8.42	8.47	8.40	8.39	8.13	8.07	8.14			
160	9.38	9.35	9.10	9.07	9.26	9.35	9.40	9.40	9.03	8.95	9.01	8.88	8.87	8.64	8.61	8.74			
165	9.87	9.80	9.49	9.48	9.63	9.73	9.70	9.90	9.62	9.49	9.42	9.34	9.32	9.12	9.12	9.29			
170	10.2	10.1	9.85	9.82	9.92	10.0	10.00	10.1	10.1	9.85	9.79	9.74	9.70	9.57	9.60	9.77			
175	10.5	10.4	10.1	10.1	10.1	10.2	10.2	10.3	10.5	10.2	10.1	10.0	10.0	9.91	9.98	10.1			
180	10.7	10.4	10.2	10.2	10.2	10.2	10.2	10.4	10.7	10.4	10.3	10.2	10.2	10.2	10.2	10.3			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:KEVINLI
Test Date:2017-12-23

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.400
Humidity:65.0%
Test Distance:7.310m [K=1.0000]
Remarks: